

# D-5600

Primer

**DAEHEUNG CHEMICAL**

D-5600 is a synthetic rubber base adhesive, which is excellent in bonding strength and spray workability. In particular, product can be used as adhesive primer for PVC FILM.

## 1. Uses

- For bonding PVC film(interior).
- For bonding melamine sheet.
- For bonding EDGE of furniture and wood.
- For bonding various plastics.
- For bonding Insulation such as a glass fiber etc.

## 2. Characteristics

- Excellent in initial bonding strength and final bonding strength.
- Excellent in heat resistance and water resistance.
- SPRAY, Brush workability is excellent.
- Depositing a porous material, even for excellent adhesion performance.

## 3. Physical properties

Properties	Value
Main component	Chloroprene rubber
Color	Light yellow & viscous liquid
Specific gravity	0.86 g/cm <sup>3</sup> (at 20 °C)
Solid contents	11~12 % (at 105±5 °C x 3hr)
Open time	10~20 min (at 20 °C)
Viscosity	50~60 cps (at 20 °C, RION VT-04 #3)
Shelf life	9months in unbroken package under dry and cool condition

#### 4. How to use

---

- Remove all dirt, grease, water and rust from the bonding surface before applying.
- Apply it surface, and joint and press then tightly.
- Please adhesive after drying is applied to the substrate to bond the PVC during FILM adhesive film (MDF, iron plate, etc.).

#### 5. Caution

---

- Avoid direct rays of the sun and keep in cool and dry place.
- Keep out of reach of children.
- Keep it away from the fire.
- Ventilation the room well because of containing solvent.
- Don't use except for the original purpose.

#### 6. Packaging

---

- 14kg C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

#### DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,  
Gyeonggi-do, Korea.

**Telephone** 02-554-8211, 031-668-1424

**Facsimile** 02-554-8215, 031-668-1425

**Website** [www.dhcbond.co.kr](http://www.dhcbond.co.kr)



# DAEHEUNG CHEMICAL