

DM-700H(A,B)

For MDF Membrane

**DAEHEUNG CHEMICAL**

DM-700H(A,B) is two component poly-urethane base adhesive, which is the good workability and bonding strength, heat resistance for the PVC DECO film to MDF materials.

1. Uses

- Membrane bonding for profiles of chipboard, MDF, solid wood, plywood on PVC film.
- Adhesion for PVC sheet, hard board, etc.

2. Characteristics

- Good initial and final bonding strength.
- Good work ability of spray.
- Cold weather and heat resistance.
- Good flexibility.

3. Physical properties

Properties	DM-700H(A) (Resin)	DM-700(B) (Hardener)	Reference
Main component	Urethane resin	Poly isocyanate	
Color	Clear & yellow viscous liquid	Dark brown & viscous liquid	
Solid contents	11.5±1 %	20±1 %	at 105±5 °C x 3hr
Viscosity	250~500 cps	Below 200 cps	at 20 °C, BF #2, 50rpm
Mixing ratio	14	0.83	By weight
Pot life	8 hr		at 20 °C
Curing time	24 hr		at 20 °C
Shelf life	9months in unbroken package under dry and cool condition		

4. How to use

- Remove all dirt, grease, water and rust from the bonding surface before applying
- For hand mixing, combine Part A and Part B in the correct ratio and mix thoroughly.

(Mixing ratio is A:B=14:0.83 by weight.)

- Spray gun Diameter : 1.0~2.5 mm
- Press : 5~6 Kg/cm²
- Applying amount: 150~200 g/m²

TECHNICAL DATA SHEET – DM 700H(A,B)

- Dry condition : 30 min (20~25 °C)
- Chamber temperature and press time : 120±10 °C , above 120 sec

- Use profile membrane machines.

5. Caution

- Avoid direct rays of the sun and keep in cool and dry place.
- Use the adhesive within pot-life.
- Close the cap tightly after using it.
- Ventilation the room well because of containing solvent.
- Don't use except for the original purpose.

6. Packaging

- DM-700H(A) [Resin]: 14kg Tin C/N
- DM-700H(B) [Hardener]: 835g PE C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,
Gyeonggi-do, Korea

Telephone +82-2-554-8211, +82-31-668-1424

Facsimile +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr



DAEHEUNG CHEMICAL