DH-2000(고) NEW





DAEHEUNG CHEMICAL

DH-2000($\ \ \, \ \ \, \ \ \,$ NEW is water-born synthetic rubber base adhesive, which is excellent in workability and not to include organic solvent so not concerned about toxicities.

This adhesive is use for as a water-born primer when pressure-sensitive adhesive PVC film.

1. Uses

• When PVC film (interior film) bonding, as a primer.

2. Characteristics

- Excellent in initial bonding strength.
- Not flammable.
- Not addictive for organic solvents.
- Depositing a porous material, even for excellent adhesion performance.

3. Physical properties

Properties	Value
Main component	Synthetic rubber latex
Color	Milk-white and viscous liquid
Solid contents	50~54 % (at 105±5 ℃ × 3hr)
Viscosity	2,000~2,400 cps (BF#2, 20rpm, 20°C)
Open time	5~15 min (at 20℃)
Dilution material	Water
Specific gravity	Above 1.0~1.1 g/cm³ (at 20 ℃)
pH	6~8
Shelf life	9 months in unbroken package under dry and cool condition

4. How to use

- Remover all dirt, grease, water and rust from the surface before applying.
- Please adhesive after drying is applied to the substrate to bond the PVC during FILM adhesive film.
 (MDF, Iron plate, etc.)

5. Caution

- Avoid direct rays of the sun and keep in cool and dry place.
- Store at room temperature.
- Keep out of reach of children.
- Close the cap tightly after using it.
- Don't use except for the original purpose.

6. Packaging

• 1kg, 3kg PE

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,

Gyeonggido, Korea

Telephone +82-2-554-8211, +82-31-668-1424 **Facsimile** +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr

