DH-2000(NH) NEW





DH-2000(NH)NEW is water-born synthetic rubber base adhesive, which is excellent in workability and not to include organic solvent so not concerned about toxicities. This adhesive is use for as a water-born primer when pressure-sensitive adhesive PVC film.

1. Uses

• When PVC film (Interior film) bonding, as a primer.

2. Characteristics

- Excellent in initial bonding strength.
- Not flammable.
- Not addictive for organic solvents.
- Depositing a porous material, even for excellent adhesion performance.

3. Physical properties

Properties	Value
Main component	Synthetic rubber latex
Color	Light gray viscous liquid
Solid contents	60±2 % (at 105±5 ℃ × 3hr)
Viscosity	6,000~7,000 cps (at 25 °C, Brookfield #2, 20rpm)
Open time	5~10 min (at 20 ℃)
Shelf life	9 months in unbroken package under dry and cool condition

4. How to use

- Remover all dirt, grease, water and rust from the surface before applying.
- Please adhesive after drying is applied to the substrate to bond the PVC during FILM adhesive film.
 (MDF, Iron plate, etc.)

5. Caution

- Avoid direct rays of the sun and keep in cool and dry place.
- Store at room temperature.
- Keep out of reach of children.
- Close the cap tightly after using it.
- Don't use except for the original purpose.

6. Packaging

• 1kg, 3kg PE

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,

Gyeonggi-do, Korea

Telephone +82-2-554-8211, +82-31-668-1424 **Facsimile** +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr

